



MS41IP 031

SAT multi-switch 5/4 with LAN Function

- SAT IP Multiswitch to convert the normal SAT signal to IP
- The switch has 4 tuner inputs for use with Quattro Band-, Quad- oder Unicable- LNB
- IP-output signal via RJ45/Ethernet socket for the connection to a network (Router)
- Distribution of the IP-signals by LAN / W-LAN or Power-Line for up to 4 network clients
- All devices connected need to support the SAT>IP protocol. These clients can be f. ex. tablet-PCs, smartphones oder notebooks with matching software or an App with SAT>IP protocol

Technical Specifications

Outputs	4x F-Connectors (SAT/FM/VHF/UHF/LAN)
Inputs	4x F-sockets (SAT - V/H, V/L, H/H, H/L) 1x USB(A)-socket for Firmware Update
Frequency range	SAT 950-2150 MHz
Data transfer	Ethernet 10/100/1000 MBps
Demodulator	Dual QPSK/8PSK Demodulator, DVB-S, DVB-S2
Current dissipation	100 - 220 V AC / 12 V DC max. 5 A/30 W (ext. power adaptor)
Operating temperature	0°C to +70°C / indoor
Colour	White
Weight	400 g
Dimensions (W x H x D)	250 x 125 x 35 mm

PP €
 RRP €
 Order No. MS41IP 031



4 004005 233605

product.info